

# ***1.5T Walking Electric Stacker***

CDD15





## SPECIFICATIONS

|                 |      |                                                  |            |                         |      |      |      |      |      |      |
|-----------------|------|--------------------------------------------------|------------|-------------------------|------|------|------|------|------|------|
| Characteristics | 1.1  | Manufacturer                                     | Unit       | JAC                     |      |      |      |      |      |      |
|                 | 1.2  | Model                                            |            | CDD15                   |      |      |      |      |      |      |
|                 | 1.3  | Power unit                                       |            | electric                |      |      |      |      |      |      |
|                 | 1.4  | Operation                                        |            | pedestrian              |      |      |      |      |      |      |
|                 | 1.5  | Rated traction weight                            | kg         | 1500                    |      |      |      |      |      |      |
|                 | 1.6  | Load center distance                             | mm         | 600                     |      |      |      |      |      |      |
|                 | 1.7  | Axle centre to fork face                         | mm         | 720                     |      |      |      |      |      |      |
|                 | 1.8  | Wheel base                                       | mm         | 1167                    |      |      |      |      |      |      |
| Weights         | 2.1  | Service weight (with battery)                    | kg         | 415                     | 460  | 477  | 495  | 503  | 515  | 525  |
| Wheels/Tyres    | 3.1  | Tires                                            |            | PU                      |      |      |      |      |      |      |
|                 | 3.2  | Driving wheel size                               | Φ×w(mm)    | Φ210×70                 |      |      |      |      |      |      |
|                 | 3.3  | Bearing wheel size                               | Φ×w(mm)    | Φ80×70                  |      |      |      |      |      |      |
|                 | 3.4  | Additional wheels (dimensions)                   | Φ×w(mm)    | Φ115×55                 |      |      |      |      |      |      |
|                 | 3.5  | Wheels, number front/rear (x = driven)           |            | 1x+1/4                  |      |      |      |      |      |      |
|                 | 3.6  | Track width                                      | mm         | 522                     |      |      |      |      |      |      |
|                 | 3.7  | Track width                                      | mm         | 410/535                 |      |      |      |      |      |      |
| Dimensions      | 4.1  | The max. lifting height                          | mm         | 1600                    | 2000 | 2500 | 3000 | 3300 | 3500 | 4000 |
|                 | 4.2  | Load capacity on Max. height                     | kg         | 1500                    | 1300 | 1100 | 900  | 800  | 700  | 300  |
|                 | 4.3  | Extended mast height                             | mm         | 2015                    | 2452 | 2952 | 3452 | 3752 | 3952 | 4452 |
|                 | 4.4  | Lowered mast height                              | mm         | 2015                    | 1495 | 1745 | 1995 | 2145 | 2245 | 2495 |
|                 | 4.5  | Free lifting height                              | mm         | 1600                    | 0    | 0    | 0    | 0    | 0    | 0    |
|                 | 4.6  | Height of handle in drive position min./max.     | mm         | 700/1225                |      |      |      |      |      |      |
|                 | 4.7  | Lowered fork height                              | mm         | 86                      |      |      |      |      |      |      |
|                 | 4.8  | Overall length                                   | mm         | 1740                    |      |      |      |      |      |      |
|                 | 4.9  | Length to fork face                              | mm         | 590                     |      |      |      |      |      |      |
|                 | 4.10 | Overall width                                    | mm         | 795                     |      |      |      |      |      |      |
|                 | 4.11 | Fork dimensions                                  | s/e/l (mm) | 60/160/1150             |      |      |      |      |      |      |
|                 | 4.12 | Width of forks                                   | mm         | 570/695                 |      |      |      |      |      |      |
|                 | 4.13 | Min.Ground clearance                             | mm         | 26                      |      |      |      |      |      |      |
|                 | 4.14 | Aisle width with pallet 1000 x 1200 across forks | mm         | 2074                    |      |      |      |      |      |      |
|                 | 4.15 | Aisle width with pallet 800 x 1200 along forks   | mm         | 2040                    |      |      |      |      |      |      |
|                 | 4.16 | Min.Turning radius                               | mm         | 1342                    |      |      |      |      |      |      |
| Performance     | 5.1  | Travel speed,laden/unladen                       | km/h       | 4.0/4.2                 |      |      |      |      |      |      |
|                 | 5.2  | Lifting speed, with/without load                 | mm/s       | 92/136                  |      |      |      |      |      |      |
|                 | 5.3  | Lowering speed, with/without load                | mm/s       | 112/98                  |      |      |      |      |      |      |
|                 | 5.4  | Maximum climbing ability, with/without load      | %          | 6/8                     |      |      |      |      |      |      |
|                 | 5.5  | Service brake                                    |            | electromagnetic braking |      |      |      |      |      |      |
| Drive           | 6.1  | Drive motor, 60 minute rating                    | kW         | 0.75                    |      |      |      |      |      |      |
|                 | 6.2  | Lift motor rating at S3 15%                      | kW         | 2.2                     |      |      |      |      |      |      |
|                 | 6.3  | Battery according to DIN 43531/35/36 A,B,C,no    |            | no                      |      |      |      |      |      |      |
|                 | 6.4  | Battery voltage                                  | V/Ah       | 2×12/100                |      |      |      |      |      |      |
|                 | 6.5  | Battery weight (± 5%)                            | kg         | 2×27                    |      |      |      |      |      |      |
| Others          | 7.1  | Type of drive control                            |            | DC power                |      |      |      |      |      |      |
|                 | 7.2  | Noise level at operator's ear                    | dB(A)      | 69                      |      |      |      |      |      |      |
|                 | 7.3  | Steering type                                    |            | Mechanical steering     |      |      |      |      |      |      |

The company reserves the right to change the parameters without notice.

**PT. SUTEJA KARYA YAMA**  
Authorized Dealer



🏠 : Jl. Joglo Raya No. 2, Joglo, Kembangan, Jakarta Barat, 11640

☎ : 0818881515

🌐 : [www.jacforklift.co.id](http://www.jacforklift.co.id)

✉ : [sales@jacforklift.co.id](mailto:sales@jacforklift.co.id)